

SERIES	HÌNH ẢNH	MÃ HÀNG	THÔNG SỐ KỸ THUẬT	GIÁ	
HBD		HBDB85H00E	Power : 85W Lumen output : 13,600lm Efficacy : 160lm/w Weight : 8.5kg	CRI : >80 CCT : 4000K/5000K Optics : 100° Input voltage : 120-277V Power factor : ≥ 0.95 Operating temp : Ta : -40 ~ 60+°C Life time : > 100,000hrs	10.500.000
		HBDBC5H00E	Power : 125W Lumen output : 19,500lm Efficacy : 156lm/w Weight : 8.5kg		12.500.000
		HBDBF5H00E	Power : 150W Lumen output : 25,700lm Efficacy : 171lm/w Weight : 9kg		13.500.000
		HBDBK5H00E	Power : 200W Lumen output : 32,100lm Efficacy : 161lm/w Weight : 9kg		14.800.000
		HBDBR5H00E	Power : 260W Lumen output : 42,400lm Efficacy : 163lm/w Weight : 9kg		16.000.000
SBD		SBDBH4H00E	Power : 170W Lumen output : 25,300lm Efficacy : 149lm/w	CRI : >80 CCT : 4000K /5000K Optics : 100° Input voltage : 120-277V Power factor : ≥ 0.95 Operating temp : Ta : -40 ~ 60+°C Life time : > 100,000hrs Weight : 4,5kg	9.500.000
		SBDBN4H00E	Power : 210W Lumen output : 29,900lm Efficacy : 142lm/w		10.500.000
		SBDBO4H00E	Power : 260W Lumen output : 35,800lm Efficacy : 139lm/w		12.000.000
		SBDBH4600E	Power : 170W Lumen output : 23,300lm Efficacy : 137lm/w	CRI : >80 CCT : 4000K /5000K Optics : 60° Input voltage : 120-277V Power factor : ≥ 0.95 Operating temp : Ta : -40 ~ 60+°C Life time : > 100,000hrs Weight : 4,5kg	10.000.000
		SBDBN4600E	Power : 210W Lumen output : 27,500lm Efficacy : 131lm/w		11.000.000
		SBDBO4600E	Power : 260W Lumen output : 32,900lm Efficacy : 127lm/w		12.500.000

LCD		LCDB85900E	Power : 85W Lumen output : 12,100lm Efficacy : 142lm/w	CRI : >80 CCT : 4000K/5000K IP65 Input voltage : 120-277V Power factor : ≥ 0.9 Operating temp : Ta : -20 ~ +40°C Life time : > 100,000hrs Weight : 5,5kg	6.200.000
		LCDBD5900E	Power : 130W Lumen output : 18,500lm Efficacy : 142lm/w		6.700.000
		LCDBF5900E	Power : 155W Lumen output : 21,000lm Efficacy : 135lm/w		7.500.000
PG		PG545ILF1N	Power : 45W Product variation : 1,600mm Lumen output : 6,000lm Efficacy : 133lm/w Weight : 1kg	CRI : >80 CCT : 4000K /5000K/5700K IP66 /IK10 Input voltage : AC220/240V Operating temp : Ta : -30 ~ 40°C Life time : > 50,000hrs	2.500.000
		PG556ILF1N	Power : 56W Product variation : 1,600mm Lumen output : 7,500lm Efficacy : 133lm/w Weight : 1,4kg		2.800.000
		PG556ILH1N	Power : 66W Product variation : 1,600mm Lumen output : 9,000lm Efficacy : 136lm/w Weight : 1,4kg		3.000.000
		PG577ILH1N	Power : 77W Product variation : 1,600mm Lumen output : 11,000lm Efficacy : 142lm/w Weight : 1,6kg		3.400.000
SLDF		SLDF7Y2M1BE	Power : 70W Lumen output : 9,450lm Efficacy : >130lm/w	CRI : >80 CCT : 3000K /4000K/5000K IP66 Input voltage : 220-240V Power factor : ≥ 0.95 Certification : CE	7.500.000
		SLDF9Y2M1BE	Power : 90W Lumen output : 12,330lm Efficacy : >130lm/w		8.500.000
		SLDFAY2M1BE	Power : 100W Lumen output : 13,400lm Efficacy : >130lm/w		9.500.000
		SLDFCY2M1BE	Power : 120W Lumen output : 15,360lm Efficacy : >125lm/w		10.000.000
		SLDFEY2M1BE	Power : 140W Lumen output : 20,250lm Efficacy : >130lm/w		12.000.000
		SLDFIY2M1BE	Power : 180W Lumen output : 25,200lm Efficacy : >130lm/w		13.000.000
FPL100		FPL100 30W	Power : 30W Efficacy : 110lm/w	CRI : >80 CCT : 4000-5000-6000K Input voltage : 220-240V Power factor : ≥ 0.95 Certification : CE Life time : > 50,000hrs	3.300.000
		FPL100 40W	Power : 40W Efficacy : 100lm/w		3.500.000

* Giá trên chưa bao gồm 10% VAT và phí lắp đặt